



GP

GENERAL PETROLEUM

Towards

GROWTH & PROSPERITY

www.generalpetroleum.de

Product Data Sheet (PDS)



GP DEOGEN SYNTHETIC 10W40 CK-4

Published By:

Technical Department of
General Petroleum GmbH
Frankfurt, Germany

Last Update Date:

1/8/2022

GP DEOGEN SYNTHETIC SAE 10W40 API CK-4



DEOGEN Synthetic 10W-40 is the premium choice for API CK-4 emission-quality diesel oil required for newer diesel engines, as well as older diesel applications (including those equipped with turbochargers). It delivers extraordinary lubrication in diesel engines found in commercial, fleet and personal vehicles. Formulated with the latest additive and synthetic base oil technology, DEOGEN Synthetic 10W-40 exceeds the higher performance demands of modern engines. It withstands the stress of heat, soot and acids to help prevent deposits, corrosion and wear. It is compatible with all exhaust treatment devices and have fuel economy performance.

PERFORMANCE STANDARDS:

GP DEOGEN SYNTHETIC 10W40 CK-4 meets and exceeds the following Industry Specifications:

API: CK-4, CJ-4, CI-4 Plus, CI-4, CH-4, SN

ACEA: E9, E7

Caterpillar: ECF-3, ECF-2

Cummins: CES 20086, CES 20081

Deutz DQC III-10 LA

Detroit Fluids Specification (DFS): 93K222, 93K218

IVECO: TLS E9 (Meets Requirements)

JASO DH-2

Mack: EOS-4.5, EO-O Premium Plus

MAN: M3575

MTU Category 2.1

MB-Approval 228.31

Renault VI: RLD-4, RLD-3

Volvo: VDS-4.5, VDS-4

FEATURES & BENEFITS:

GP DEOGEN SYNTHETIC 10W40 CK-4 provides:

- Excellent engine cleanliness through advanced soot handling technology.
- Mixed fleet capabilities.
- Exceptional low engine wear.
- Trouble free operation between long drain service intervals.
- Reduced maintenance capabilities.
- Low Oxidation
- All season engine oil

GP DEOGEN SYNTHETIC SAE 10W40 API CK-4

APPLICATIONS:

- Commercial road transport, including the latest engines fitted with exhaust cleanup devices of all types
- Mixed fleets of both diesel and gasoline engines, and both old and new equipment
- Stop-and-go vehicles in high soot loading service such as buses and waste collection trucks
- Most modern off-highway engines including those adapted for current and future emissions standards

TECHNICAL DATA

Sr. No	Characteristics	Test Method	Results
01	Appearance	VISUAL	B & C
03	Color	ASTM D-1500	L3.5
04	Density @ 15 C, g/ml	ASTM D-4052	0.868
05	Viscosity @ 40 C, cSt	ASTM D-445	106
06	Viscosity @ 100 C, cSt	ASTM D-445	15.5
07	Viscosity Index	ASTM D-2270	155
08	TBN, mg KOH/gm	ASTM D-2896	12.0
09	Flash Point, COC, C	ASTM D-92	220
10	Pour Point, C	ASTM D-97	-39
10	CCS Viscosity (mPa·s)-25	ASTM D-5293	6700

GP DEOGEN SYNTHETIC SAE 10W40 API CK-4



Health and Safety:

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.