

GROWTH & PROSPERITY

www.generalpetroleum.de

Material Safety Data Sheet (MSDS)



GP SYNCROGEN SYNTHETIC ATF DEX III

Published By:

Technical Department of General Petroleum FZE

Last Update Date:

1/8/2022



SECTION #1:

PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME: GP SYNCROGEN SYNTHETIC ATF DEX III

MANUFACTURER/SUPPLIER'S NAME:

GENERAL PETROLEUM FZE PLOT.3E-02, 2J-01, 02 HAMRIYA FZE, PHASE-1 SHARJAH, UAE P.O. BOX 53046, SHARJAH, UAE TEL: 00971 6 5754717 FAX: 00971 6 5754718

24 HOURS EMERGENCY: Call GP LUBE (800-475823)

PRODUCT USE: AUTOMATIC TRANSMISSION FLUID

SECTION #2: COMPOSITION/INFORMATION ON INGREDIENTS

PREPARATION

CHEMICAL NATURE:

Petroleum-derived severely refined mineralbase product.

SUBTANCES CONTRIBUTING TO HAZARDS:

No component is present at sufficient concentration to require a hazard classification for health in accordance with EC Directives.

IMPURITIES CONTRIBUTING TO HAZARDS: None to our knowledge.

SECTION #3:

HAZARD IDENTIFICATION

ADVERSE HUMAN HEALTH EFFECTS:Under normal conditions of use, the product
holds no danger of intoxication.ENVIRONMENTAL EFFECTS:Don't reject this product into
the environment.PHYSICAL AND CHEMICAL HAZARDS:No specific risk of fire or explosion under
normal conditions of use.

General Petroleum FZE



SECTION #4: FIRST AID MEASURES IN CASE OF SERIOUS MANIFESTATIONS, CALL IN A DOCTOR OR EMERGENCY MEDICAL CARE **ROUTE OF EXPOSURE: INHALATION:** Inhalation of heavy concentrations of vapour, fumes or spray, may cause mild irritation of the throat. Transport the person into fresh air, keep warm and allow to rest. Immediately remove all soiled or stained clothing. Wash the affected area immediately and repeatedly with soap **CONTACT WITH THE SKIN:** and water. Keep eyes open and rinse immediately and repeatedly with water for at least 15 minutes Possible risk of vomiting and CONTACT WITH THE EYES: diarrhea **INGESTION:** Do not induce vomiting to avoid the riskof aspiration into the respiratory tract Give nothing to drink. **ASPIRATION:** If the product is believed to have entered the lungs (in case of vomiting, for example), take the person to hospital for immediate care

SECTION #5:

FIRE FIGHTING MEASURES

FLASH POINT (COC):

AUTOIGNITION TEMPERATURE (°C):

EXTINGUISHING MEDIA:

HAZARDOUS COMBUSTION PRODUCTS:

SPECIAL FIRE FIGHTING PROCEDURES:

200°C

N/A

Foam, Dry chemical and CO₂.

Normal combustion products, CO and CO_2 .

Do not enter confined fire space without adequate protective clothing and an approved positive self-contained breathing apparatus. Use water to cool fire exposed containers.



SECTION #6:

ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK PROCEDURES:

Eliminate all ignition sources. Stop leak only if safe to do so. Absorb residue or small spills with absorbent material and remove to non-leaking containers for disposal.

HANDLING AND STORAGE **SECTION #7:** STORAGE AND HANDLING: Store in cool, dry, ventilated area, away from heat and ignition sources. Use good personal hygiene. Always keep the container close. **PREVENTION OF FIRE & EXPLOSION:** Empty containers may contain flammableor **Explosive vapours Product**impregnated cloths and paper or material used to mop up spills can constitute a fire hazard. Do not allow these to accumulate in a pile. Discard these with all safety precautions immediately after use. PRECAUTIONS: Avoid static electricity build up with Avoid static electricity build up w connection to earth. By arranging and setting up machinery and equipment so as to avoid accidental spills and splashes onto hot machine parts and electrical contacts. TO BE AVOIDED: Do not store exposed to the elements. **INCOMPATIBLE PRODUCTS:** Dangerous reaction with strong oxidizing Agents. **PACKAGING MATERIALS: RECOMMENDED:** Use only hydrocarbon-resistant containers, joints, pipes, etc. Keep in original container if possible; otherwise, transfer all indications on the regulatory label to the new container.



SECTION #8:	EXPOSURE CONTROLS / PERSONAL PROTECTION
VENTILATION:	Mechanical ventilation is recommended.
RESPIRATORY PROTECTION:	If mist present, chemical cartridge respirator is recommended.
GLOVES:	Resistant gloves (Viton, nitrile, Neoprene) are recommended when handling this material.
EYE PROTECTION:	Chemical safety goggles are recommended.
OTHER PROTECTION:	In confined spaces or where the risk of skin exposure is higher, resistant clothing or apron should be worn.
SECTION #9:	PHYSICAL & CHEMICAL DATA
APPEARANCE:	

PHYSICAL STATE:	Viscous Liquid
COLOR:	RED
ODOR:	Characteristic Odor of Oil
pH:	Not Applicable
FLASH POINT:	as mentioned above
AUTO IGNITION TEMPERATURE:	> 240°C (ASTM E 659). This temperature
	may be significantly lower under particular conditions (oxidation on high surface areas)
EXPLOSION LIMITS:	may be significantly lower under particular conditions (oxidation on high
EXPLOSION LIMITS: DENSITY @ 15°C:	may be significantly lower under particular conditions (oxidation on high surface areas)



VISCOSITY @ 100°C:	6.5 to 8 CST			
SECTION #10: STABILITY AND REACTIVITY				
STABILITY:	The product is stable under normal temperatures of storage, handling and use.			
DANGEROUS REACTIONS:	Not dangerous reaction known under normal conditions of use, to refer to the technical notice.			
CONDITIONS TO AVOID:	Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.			
MATERIALS TO AVOID:	Avoid contact with strong oxidizing.			
DANGEROUS DECOMPOSITON PRODUCTS:	Incomplete combustion and thermolysis produce more or less toxic gases such as CO, CO2, various hydrocarbons, aldehydes and soot.			
SECTION #11: TOXICOLOGICAL INFORMATION				
ACUTE TOXICITY/LOCAL EFFECTS				
INHALATION:	Risk is improbable under normal conditions of use. Inhalation of important concentration of vapor or aerosols may cause irritation of the upper respiratory tract.			
CONTACT WITH SKIN:	Risk is improbable under normal conditions of use.			

In case of ingestion of small quantities, no important effect observed. in case of ingestion of larger amounts: abdominal pain, diarrhea,...

INGESTION:



SENSITIZATION:

To our knowledge, the product don't induce sensitization.

CHRONIC TOXICITY OR LONG-TERM TOXICITY

CONTACT WITH THE SKIN:

CARCINOGENECITY:

Characteristic skin affections (oil blisters) may develop following prolonged and repeated exposure through contact with stained clothing.

This product is not regarded as carcinogenic. During use in engines, contamination of oil with low levels of combustion products occur. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

SECTION #12: ECOLOGICAL INFORMATION MOBILITY AIR: there is a slow loss by evaporation. GROUND: Given its physical and chemical characteristics, the product generally shows little mobility in the ground. WATER: The product is insoluble; it spreads on the surface of the water. PERSISTENCE AND DEGRADABILITY: Experimental data on the finished product are not Available. However, the "mineral oil" portion of the virgin product is intrinsically biodegradable. Particular ingredients may

not be biodegradable.



ECOTOXICITY:	The virgin product is considered to presentno danger for land-growing organisms and little danger for aquatic life. No data are currently available for the used product.	
SECTION #13: DISPOSABL	E CONSIDERATIONS	
WASTE DISPOSAL:	Dispose in a safe manner in accordance with local/national regulations. If need be, collection by an authorized waste contractor and regeneration or incineration in an approved installation.	
WASTE CLASS:	13-02-02 (non-chlorinated engine, gear, lubricating oils) The waste classification is dependent on the composition of the product at the time of disposal. The waster producer is responsible for correct specification of the waste and also should be in arrangement with the authorized waste disposal company.	
DISPOSAL OF CONTAMINATED PACKAGING:	Proceed in compliance with prevailing regulations.	

SECTION #14: TRANSPORT INFORMATION

Land (as per ADR classification): Not regulated

This material is not classified as dangerous under ADR regulations.

IMDG: This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply): This material is either not classified as dangerous under IATA regulations or needs to follow country specific requirements.



	r		1
	LAND TRANSPORT	SEA TRANSPORT (IMDG	AIR TRANSPORT
	(ADG)	/ IMO)	(IATA / ICAO)
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping	Not regulated.	Not regulated.	Not regulated.
name			
Transport hazard	Not regulated.	Not regulated.	Not regulated.
class(es)			
Packing group	Not applicable	Not applicable	Not applicable
Environmental	No.	No.	No.
hazards			
Special precautions	-	-	-
for user			

SECTION #15:

REGULATORY INFORMATION

EUROPEAN REGULATIONS:

EC LABELLING:	
SYMBOLS (S)	None
R PHRASES	None
S PHRASES	None

SECTION #16:

ADDITIONAL INFORMATION

We believe that technical information and recommendations contained herein to be reliable and accurate. However, we provide these data without warranty or guarantee of any kind, expressed or implied. We assume no responsibility for any loss, damage, or expense, direct or consequential, arising from the use of products described herein.