



www.generalpetroleum.de

Product Data Sheet (PDS)



GP MARGEN MARINE 5040 (GSX)

Published By: Quality

Control Department of
General Petroleum GmbH
Frankfurt, Germany

Last Update Date:

1/8/2023

Marine cylinder oil is formulated for low sulphur residual fuel blends and distillates.

Product Description:

GP MARGEN MARINE 5040 (GSX) has been developed to cope with sludge and deposit forming tendencies of certain blended fuels. These fuels have lower corrosion potential but may tend to form more deposits. The cylinder oil is formulated to have enhanced detergency properties and excellent dispersancy, wear and oxidation resistance properties. GP MARGEN MARINE 5040 (GSX) is approved for the latest 2-stroke low speed crosshead engines operating at higher BMEP and liner temperatures.

Features & Benefits:

- Advanced detergency properties minimise deposits and the formation of sludges, protecting against piston ring stick and ring groove deposits.
- Lower ash forming formulation, avoids crown land deposit formation, even when running of very low sulphur fuels.
- Excellent anti-wear properties similar to the characteristic low cylinder liner wear of the GP MARGEN MARINE range of cylinder oils.
- Tested and compatible with all standard seal materials.
- High levels of ring pack cleanliness and anti-wear enables extended time between piston overhauls.

Applications:

- Cylinder lubrication of the latest, highly rated low speed crosshead marine diesel engines operating on blended residual fuels and distillates with sulphur below 0.50%.
- The feed rates as recommended by the manufacturer should be maintained and in accordance with engine operating conditions. Higher feed rates may be required for running-in.
- GP MARGEN MARINE is suitable for use in vessels running on MARPOL Annex VI Regulation 14 compliant fuels with maximum sulphur of 0.50%.

TECHNICAL DATA:

Sr. No	Characteristics	Test Method	Results
01	SAE		50
02	TBN		40
03	Viscosity @ 100 0C, cSt	D 445	19.9
04	Viscosity Index	D 2270	105
05	Flash Point, 0C	D 92	270
06	BN, mg KOH/g	D 2896	40
07	Pour Point, 0C	D 97	-18
08	Density @ 15 0C, kg/l	D 4052	0.9161

Health and Safety:

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

