



GP

Lubricants

GROWTH & PROSPERITY

www.generalpetroleum.de

Product Data Sheet (PDS)



GP INGEN HYDRAULIC MINERAL OIL 10W AW

Published By:

Technical Department of
General Petroleum FZE

Last Update Date:

11/1/2024

GP INGEN HYDRAULIC MINERAL 10W AW



GP INGEN HYDRAULIC MINERAL 10W AW are premium high-viscosity-index hydraulic fluid for wear protection. They are produced from high quality and low-contaminant paraffinic base oils which provide long service life. It contains anti-wear and antioxidant additives. They are also improved their viscosity index by adding viscosity index improver (viscosity modifier) which are able to use in broad temperature range and improve system efficiency

PERFORMANCE STANDARD:

GP INGEN HYDRAULIC MINERAL 10W AW meets and exceeds the following specifications:

- Bosch Rexroth RDE 90235
- SEB 181222
- PARKER HF-0/HF-1/HF-2
- DIN 51524-3
- ISO 11158
- JCMAS HK P041
- GB 11118.1-2011
- ASTM D6158
- AIST 126, 127

FEATURES & BENEFITS:

- Maximize protection from wear, corrosion and suitable for using with rubber seals without adverse reaction.
- Antifoaming characteristics
- High oxidation resistance
- Good water separating characteristics minimize the formation of emulsions
- Provide shear stability characteristics and stay-in-viscosity-grade in various temperatures.

APPLICATIONS:

- Designed for use in hydraulic systems subjected to wide variations in operating temperatures.
- Suitable for hydraulics of mobile, construction and agricultural equipment.

GP INGEN HYDRAULIC MINERAL 10W AW



- Recommended for general hydraulic applications requiring anti-wear type oil.
- Can be used as R&O (Rust & Oxidation Inhibited) oil.

TECHNICAL DATA

Sr. No	Characteristics	Test Method	10W
01	Appearance	VISUAL	B & C
02	Density @ 15 C, g/ml	ASTM D-4052	0.860
03	Viscosity @ 40 C, cSt	ASTM D-445	39.44
04	Viscosity @ 100 C, cSt	ASTM D-445	6.82
05	Viscosity Index	ASTM D-2270	131
06	Flash Point, COC, C	ASTM D-92	222
07	Pour Point, C	ASTM D-97	-33

GP INGEN HYDRAULIC MINERAL 10W AW



Health and Safety:

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Material Safety Data Sheet (MSDS).

MSDSs are available upon request. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

GP INGEN HYDRAULIC MINERAL 10W AW

