



GP

GENERAL PETROLEUM

www.generalpetroleum.de

Product Data Sheet (PDS)



GP SYNCROGEN SYNTHETIC ATF DEX VI

Published By:

Technical Department of
General Petroleum GmbH
Frankfurt, Germany

Last Update Date:

1/8/2023

GP SYNCROGEN SYNTHETIC ATF



GP SYNCROGEN SYNTHETIC ATF DEX VI is a high performance, fully synthetic automatic transmission fluid that meets or exceeds the stringent requirements of DEXRON® VI specification and provides warranty protection for 2006 and newer General Motor's vehicles. It also provides improved performance in older vehicles, wherever DEXRON is specified.

PERFORMANCE STANDARDS:

GP SYNCROGEN SYNTHETIC ATF DEX VI meets or exceeds the following specifications (but not limited

to):

GM DEXRON VI, DEXRON II, DEXRON IID, DEXRON IIE, DEXRON IIIG, DEXRON IIH, MERCON® LV, Toyota ATF WS, T III, T IV, JASO 1A(03) JASO 1A LV(13), Honda ATF-Z1 (except in CVTs), Honda DW-1, (Hyundai/Kia SP-IV, SP-IV M, SP-III, Dex-II/ SP-II, SP-II M, JWS 3314), (Nissan Matic Fluid C, D, J, K, S, W), (Opel/GM 19 40 700, Opel/GM 19 40 767), (Peugeot ZF 4HP20, Peugeot/Citroen Z 000169756), (Porsche ZF 5HP19FL, ZF 5HP20, LT71141, ATF 3403-M115, T-IV, JWS 3309), (PSA B71 2340), (Renault DPO/AL4, Renault Matic D2), (Suzuki ATF AW-1, S, AT OIL 5D06, ATF 2326, ATF 2384K, JWS 3309, ATF 3314, ATF 3317), (Volvo 97325, 97335, CE 97340), (VW 5 HP (ZF 5 HP 30), VW 5HP (18FL, 30), VW 5HP (19FL, 24A), VW TL 52540-A, VW TL 521 62, ZF all 3 & 4 speed transmission), (ZF 6 speed transmissions, ZF TE-ML 05L, ZF TE-ML 09, ZF TE-ML 11A, 11B, ZF TE-ML 21L), (Mitsubishi Diaqueen SK, SP, SP-II, SP-III, SP-IV, AW, J2, J3, ATF-MA1, ATF PA), (Mazda ATF D-II, ATF M-III, ATF M-V, ATF FZ, ATF A7, ATF F-1, ATF S-1, ATF N-1, ATF 3317), (MB ZF 4HP20), (MINI COOPER T-IV), (Land Rover TYK500050, LR0022460), (Lexus JWS 3309), (MAN 339A), (JASO M315-2013 1A, M315-2013 1A-LV, M315-2013 2A), (Jaguar ATF 3403 M115, ATF 3403-M115, LT71141, ZF 5HP24, JLM20238, ATF 3403 JLM20238, K17, JLM 20292, Jaguar Fluid 8432, Jaguar WSS-M2C922A1), (ISUZU ATF WSI, BESCO ATF-II, BESCO ATF-III, 08200-9001, ZF 8 speed transmissions, ZF 9 speed transmissions)

APPLICATION:

For most 2006 and newer GM vehicles.

ADVANTAGES:

- Low viscosity formulation provides fuel economy benefits compared with fluids formulated to meet DEXRON® IIIH or earlier specifications.
- Premium synthetic formulation gives outstanding oxidative resistance extending transmission life
- Enhanced friction durability improves shifting performance.

TECHNICAL DATA

Sr. No	Characteristics	Test Method	Results
01	Appearance	VISUAL	B & C
02	Color	ASTM D-1500	Red
03	Density @ 15 C, g/ml	ASTM D-4052	0.868
04	Viscosity @ 40 C, cSt	ASTM D-445	27.86
05	Viscosity @ 100 C, cSt	ASTM D-445	6.0
06	Viscosity Index	ASTM D-2270	170
07	Flash Point, COC, C	ASTM D-92	218
08	Pour Point, C	ASTM D-97	-45

Health and Safety:

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.